



PE TERMINAL WITH SCREW CONNECTION,
SECTION: 35 - 95 MM², AWG: 2 - 4/0,
WIDTH: 25 MM, COLOR: GREEN-YEL.

Similar to image

Technical data:

Mounting type		DIN rail 35 mm
Length	mm	83
Color		green-yellow
Height / with lowest-profile installation	mm	96.5
Number of terminal levels		2
Number of terminal points / per terminal level		1
Product feature / PEN function		Yes
Combustibility class acc. to UL 94		V0
Terminal contact spacing	mm	25
Position / of terminal		lateral
Product component / required / connection plate		No
Ambient temperature		
• during operating	°C	-25 ... +35
Design of the electrical connection		
• 1		screw-type terminal
• 2		screw-type terminal
Conductor cross-section that can be connected		
• solid	mm ²	25 ... 95

- multibrin
- finely stranded
 - with wire end processing
 - without wire end processing

mm ²	25 ... 95
mm ²	25 ... 95
mm ²	35 ... 95

Certificates/approvals:

General Product Approval



Declaration of Conformity



Shipping Approval



Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WH1000-0CQ07>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WH1000-0CQ07/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH1000-0CQ07

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Mar 17, 2014