SIEMENS

Product data sheet LZS:PT3A5S15



PLUG-IN RELAY COMPLETE UNIT AC 115V, 3 CO CONTACT LED MODULE RED STANDARD PLUG-IN SOCKET SCREW TERMINAL 3.5 MM PINNING

General technical details:		
Supply voltage frequency / for auxiliary and control current circuit / rated value		
• minimum	Hz	50
• maximum	Hz	60
Type of voltage		AC
Control supply voltage		
• at 50 Hz / at AC / rated value		
• minimum	V	115
• maximum	V	115
• at 60 Hz / at AC / rated value		
• minimum	V	115
• maximum	V	115
Number of NC contacts		
• for auxiliary contacts		0
Number of NO contacts		
• for auxiliary contacts		0
Number of changeover contacts		
• for auxiliary contacts		3
Operating current / of the auxiliary contacts		
• at DC-13		

• at 24 V	А	8
• at AC-15		
• at 230 V	Α	5
Design of the switching function		changeover switch
• guided		No
Switching behaviour		monostable

Mechanical design:				
Design of the electrical connection		screw-type terminals		
Design of the relay operating mechanism		poled		
Product component / jumper socket		Yes		
Width	mm	28		
Height	mm	72		
Depth	mm	74		

Certificates/approvals:

General Product Approval other



Declaration of Conformity

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)

http://www.siemens.com/industrial-controls/mall

CAx-Online-Generator

http://www.siemens.com/cax

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

http://support.automation.siemens.com/WW/view/en/LZS:PT3A5S15/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

 $\underline{\text{http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=LZS:PT3A5S15}}$

last change: Jun 16, 2014