

PLUG-IN RELAY 2 CHANGEOVER CONT. AC 115V



General technical details:

Supply voltage frequency / for auxiliary and control current circuit / rated value

• minimum	Hz	50
• maximum	Hz	60

Type of voltage

AC

Control supply voltage

• at 50 Hz / at AC / rated value		
• minimum	V	115
• maximum	V	115
• at 60 Hz / at AC / rated value		
• minimum	V	115
• maximum	V	115

Number of NC contacts

• for auxiliary contacts	0
--------------------------	---

Number of NO contacts

• for auxiliary contacts	0
--------------------------	---

Number of changeover contacts

• for auxiliary contacts	2
--------------------------	---

Operating current / of the auxiliary contacts

• at DC-13	
------------	--

<ul style="list-style-type: none"> • at 24 V • at AC-15 • at 230 V 	A	8
	A	5
Design of the switching function		changeover switch
<ul style="list-style-type: none"> • guided 		No
Switching behaviour		monostable

Mechanical design:

Design of the electrical connection		screw-type terminals
Design of the relay operating mechanism		poled
Product component / jumper socket		No
Width	mm	22.5
Height	mm	28
Depth	mm	35

Certificates/approvals:

General Product Approval

other



[Declaration of Conformity](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WWW/view/en/LZX:PT270615/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=LZX:PT270615

last change:

Jun 16, 2014