

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

## **Product image**







### **Building installation wiring**

For building installations, we offer a complete system that revolves around the 10×3 copper rail and comprises perfectly coordinated components: from installation terminal blocks, neutral conductor terminal blocks and distribution terminal blocks to comprehensive accessories such as busbars and busbar holders.

### General ordering data

Version	Accessories, Clamping yoke for busbar, Rated cross-section: Clamping yoke, Feed-through (bushing)
Order No.	<u>0556700000</u>
Туре	ZB 4/6
GTIN (EAN)	4008190188412
Qty.	50 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

### **Dimensions and weights**

Depth	20 mm	Depth (inches)	0.787 inch
Height	12 mm	Height (inches)	0.472 inch
Net weight	2.88 g	Width	5.3 mm
Width (inches) 0.209 inch			
Temperatures			
Operating temperature range	For operating temperature range see EC Design Test Certificate / IEC Ex-		
	Certificate of Conformity		

#### **Material data**

Material	Steel	Colour	silver



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

## **Rating data IECEx/ATEX**

Certificate No. (ATEX)	DEMKO03ATEX136028U	ATEX certificate	DEMKO03ATEX136028U_
ATEX certificate	DEMKO03ATEX136028U_d.	·	IECEXULD13.0005U
Vire cross section max. (ATEX)	4 mm <sup>2</sup>	Wire cross section max. (IECEX)	4 mm²
Operating temperature range	For operating temperature range see EC Design Test Certificate / IEC Ex- Certificate of Conformity	Marking EN 60079-7	Ex eb II C Gb
Ex 2014/34/EU label	II 2 G D	Safety notice	Installation instructions: The potential equalisation (PE) rail modules are suitable for use in housings in atmospheres with flammable gases and dust. For use in areas with flammable gases, these housings must meet the requirements of EN 60079-0 and EN 60079-7. For use in areas with flammable dust, these housings must meet the requirements of EN 60079-0 and EN 60079-3.1. When combined with other terminal block ranges and sizes, and when other accessories are used, you must comply with the clearance and creepage distances given. Regarding accessory use, the manufacturer's instructions must be followed. List of restrictions: The PE rail modules are considered one component, with Ex marking when used with the busbar holders of type SH and WEW. When used independently, the above named components are not covered by this certificate.
System specifications			
Vorcion	for husbar 6 · · G		
Version	for busbar 6 x 6 mm		
Additional technical data			

Wire cross section max. (CSA)

Creation date March 22, 2021 10:52:13 AM CET

Certificate No. (CSA)

Wire cross section min. (CSA)

12400-237

26 AWG

10 AWG



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

## **Conductors for clamping (rated connection)**

Clamping screw	M 3	Stripping length	16 mm
Ciamping sciew	IVI 3	Stripping length	10 111111
Tightening torque, min.	1.2 Nm	Type of connection	Clamping yoke
Wire connection cross section,	finely	Wire connection cross-section	n, solid
stranded, max.	4 mm <sup>2</sup>	core, max.	6 mm²
Wire connection cross-section,	solid		
core, min.	0.5 mm <sup>2</sup>		

#### General

Installation advice	Feed-through (bushing)	

#### Classifications

ETIM 6.0	EC002848	ETIM 7.0	EC002848
ECLASS 9.0	27-14-11-92	ECLASS 9.1	27-14-11-92
ECLASS 10.0	27-14-11-92	ECLASS 11.0	27-14-11-46

#### **Approvals**

Approvals



none comoni		ROHS	Conform
-------------	--	------	---------

#### **Downloads**

Approval/Certificate/Document of	Attestation of Conformity
Conformity	ATEX Certificate
	IECEx Certificate
Engineering Data	<u>STEP</u>
Engineering Data	EPLAN, WSCAD
User Documentation	Installation Instruction
	<u>StorageConditionsTerminalBlocks</u>