

IE-PI-RJ45-FH-A-1.1

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com



RJ45 plug-in connector (no tools required) according to IEC 60603-7-51.

General ordering data

Version	Substitute wire manager, Cat.6 _A / Class E _A (ISO/IEC 11801 2010), EIA/TIA T568 A
Order No.	1992920000
Type	IE-PI-RJ45-FH-A-1.1
GTIN (EAN)	4050118377965
Qty.	30 pc(s).

Creation date March 26, 2021 7:50:22 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

IE-PI-RJ45-FH-A-1.1

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight	4.433 g
------------	---------

Temperatures

Operating temperature	-40 °C...85 °C
-----------------------	----------------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

General data

Wiring	EIA/TIA T568 A	Speed	10 GBit
Insulation cross-section, min.	0.85 mm	Insulation cross-section, max.	1.1 mm
Category	Cat.6 _A / Class E _A (ISO/IEC 11801 2010)	Contact surface	Gold over nickel
Connection diameter, solid	0.41...0.51 mm	Wire connection diameter, solid, min.	0.41 mm
Conductor connection cross-section, solid (AWG)	AWG 26...AWG 24	Wire connection diameter, solid, max.	0.51 mm
Connection diameter, flexible	0.46...0.61 mm	Wire cross-section, solid, min. (AWG)	AWG 26
Wire cross-section, solid, max. (AWG)	AWG 24	Conductor connection cross-section, flexible (AWG)	AWG 27...AWG 24
Wire connection diameter, flexible, min.	0.46 mm	Wire connection diameter, flexible, max.	0.61 mm
Wire cross-section, finely stranded, min. (AWG)	AWG 27	Wire cross-section, finely stranded, max. (AWG)	AWG 24
Conductor connection cross-section, extremely flexible	0.51, Approval of the cable by Weidmüller necessary	Conductor connection diameter, very finely stranded, min.	0.51 mm
Conductor connection cross-section, extremely flexible (AWG)	AWG 26, Approval of the cable by Weidmüller necessary	Conductor connection cross-section, very finely stranded, min. (AWG)	AWG 26
Note, very finely stranded line connection	Approval of the cable by Weidmüller necessary	Protection degree	IP20
Ability to reconnect	≤ 4 cycles (with the same cross-section)		

Electrical properties

Contact resistance	≤ 20 mΩ	Current-carrying capacity at 50 °C	1 A
Dielectric strength, contact / contact	≥ 1000 V DC	Dielectric strength, contact / shield	≥ 1500 V DC
Insulation strength	> 500 MΩ	PoE / PoE+	conforming to IEEE 802.3at

General standards

Certificate No. (cURus)	E471884	Certificate no. (cULus)	E471884
Connector standard	IEC 60603-7-51		

Classifications

ETIM 6.0	EC001121	ETIM 7.0	EC001121
ECLASS 9.0	27-44-03-90	ECLASS 9.1	27-44-03-90
ECLASS 10.0	27-44-03-90	ECLASS 11.0	27-44-03-90

Data sheet**IE-PI-RJ45-FH-A-1.1****Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germanywww.weidmueller.com**Technical data****Approvals**

Approvals



ROHS

Conform

UL File Number Search

E471884

Downloads

User Documentation

[MAN IE GUIDE DE](#)
[MAN IE GUIDE EN](#)