

**CRIMPER 25 Z****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Crimping tools for wire end ferrules, with and without plastic collars**

- Ratchet guarantees precise crimping
- Release option in the event of incorrect operation

**General ordering data**

Version	Tools, Crimping tool for wire-end ferrules, 6mm <sup>2</sup> , 25mm <sup>2</sup>
Order No.	<a href="#">9040470000</a>
Type	CRIMPER 25 Z
GTIN (EAN)	4008 19046 1485
Qty.	1 pc(s).

Creation date March 30, 2021 12:44:34 AM CEST

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

**CRIMPER 25 Z****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

Net weight	529.57 g	Weight	615 g
Width	250 mm	Width (inches)	9.842 inch

**Environmental Product Compliance**

REACH SVHC	Lead 7439-92-1
------------	----------------

**Technical data**

Description of article	Crimping tool for wire-end ferrules 6 - 25mm <sup>2</sup>	Version	Mechanical, without interchangeable inserts
------------------------	---	---------	---

**Description of contact**

Crimping range, max.	25 mm <sup>2</sup>	Crimping range, min.	6 mm <sup>2</sup>
Type of contact	Twin wire-end ferrules with/ without plastic collars		

**tool data crimping**

Crimping profile 1, max.	6 mm <sup>2</sup>	Crimping profile 2, max.	10 mm <sup>2</sup>
Crimping profile 3, max.	25 mm <sup>2</sup>	Crimping profile 4, max.	16 mm <sup>2</sup>

**Classifications**

ETIM 6.0	EC000168	ETIM 7.0	EC000168
ECLASS 9.0	21-04-38-11	ECLASS 9.1	21-04-38-11
ECLASS 10.0	21-04-38-11	ECLASS 11.0	21-04-38-11

**Important note**

Product information	Crimping range 2 (with multiple crimping positions): 10 mm <sup>2</sup> , 2 x 4 mm <sup>2</sup> , 2 x 6 mm <sup>2</sup> Crimping range 4 (with multiple crimping positions): 16 mm <sup>2</sup> , 2 x 10 mm <sup>2</sup>
---------------------	---

**Approvals**

Approvals

