

**KQN-M12/-35****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



**The use of insulated connectors guarantees users consistent electrical connection quality in the long term.**

- Wide range of insulated and non-insulated cable lugs and connectors
- Tubular cable lugs according to current market standards (Euroseries)
- Compression cable lugs acc. to DIN 46235
- Sheet metal cable lugs acc. to DIN 46234
- Insulated ring cable lugs to DIN 46237
- Insulated pin cable lugs to DIN 46231

**General ordering data**

|            |                                            |
|------------|--------------------------------------------|
| Version    | cable lug, terminal end,35 mm <sup>2</sup> |
| Order No.  | <a href="#">1493130000</a>                 |
| Type       | KQN-M12/-35                                |
| GTIN (EAN) | 4050118302837                              |
| Qty.       | 50 pc(s).                                  |

Creation date March 24, 2021 2:12:02 AM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

**KQN-M12/-35****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |        |        |        |
|------------|--------|--------|--------|
| Net weight | 11.7 g | Weight | 1.17 g |
|------------|--------|--------|--------|

**Connectors**

|                                |                    |                                |               |
|--------------------------------|--------------------|--------------------------------|---------------|
| Conductor cross-section        | 35 mm <sup>2</sup> | Connection length (l)          | 31 mm         |
| Hole                           | M 12               | Inside diameter of flange (d2) | 13 mm         |
| Inside diameter of shaft (d1)  | 9 mm               | Insulation                     | not available |
| Outside diameter of shaft (d3) | 22 mm              | Shaft length (a)               | 12 mm         |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001059    | ETIM 7.0    | EC001059    |
| ECLASS 9.0  | 27-40-02-12 | ECLASS 9.1  | 27-40-02-12 |
| ECLASS 10.0 | 27-40-02-12 | ECLASS 11.0 | 27-40-02-12 |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                  |                       |
|------------------|-----------------------|
| Engineering Data | <a href="#">EPLAN</a> |
|------------------|-----------------------|

**Data sheet**

**KQN-M12/-35**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

