

PB-DP SUB-D TERM**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly.

General ordering data

Version	SUB-D
Order No.	8460860000
Type	PB-DP SUB-D TERM
GTIN (EAN)	4032248026364
Qty.	1 pc(s).

Creation date March 29, 2021 10:54:15 PM CEST

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

PB-DP SUB-D TERM**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	16 mm	Depth (inches)	0.63 inch
Height	47.4 mm	Height (inches)	1.866 inch
Net weight	43 g	Width	64.6 mm
Width (inches)	2.543 inch		

Temperatures

Humidity	Max. 75% at +25°C, non-condensing
----------	-----------------------------------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Technical specifications for sub-D connector

BUS interface	D-Sub 9-pole, Pin	BUS, cable interface	Screw connection
Data rate	12 MBit/s	Housing main material	PC UL 94 V-1
Humidity	Max. 75% at +25°C, non-condensing	Interlock	UNC4-40
Outgoing elbow	90°	Plug-in connector and pin assignment	In accordance with the PROFIBUS specification
Programming interface	No	Protection degree	IP40
Temperature range of housing	-25...+80 °C	Terminating resistor available	Yes

Technical data customisable plug-in connectors

Cable diameter, max.	8 mm	Cable diameter, min.	4.5 mm
Housing main material	PC UL 94 V-1	Protection degree	IP40
Temperature range of housing	-25...+80 °C		

Classifications

ETIM 6.0	EC001132	ETIM 7.0	EC001132
ECLASS 9.0	27-44-03-02	ECLASS 9.1	27-44-03-90
ECLASS 10.0	27-44-03-02	ECLASS 11.0	27-44-03-02

Approvals

Approvals



ROHS

Conform