

**IE-PI-RJ45-TH****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



RJ45 inserts for plug-in connectors ver.1 / 4 / 5 / 14 and junction boxes IE-OM...; IE-OP...; IE-CC...

**General ordering data**

Version	Plug insert RJ45 IDC, Plug insert RJ45, crimp
Order No.	<a href="#">1962720000</a>
Type	IE-PI-RJ45-TH
GTIN (EAN)	4032248644834
Qty.	10 pc(s).

Creation date March 26, 2021 3:35:53 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

## IE-PI-RJ45-TH

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

Net weight	9.62 g
------------	--------

## Temperatures

Operating temperature	-40 °C...70 °C	Humidity	0...93 % rel. humidity
-----------------------	----------------	----------	------------------------

## Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

## General data

Connection 1	RJ45	Connection 2	IDC
Description of article	Plug insert RJ45, crimp	Colour	Miscellaneous
Shock resistance acc. to IEC 60512-4	250 ms <sup>-2</sup>	Vibration resistance acc. to IEC 60512-4	50 ms <sup>-2</sup> sinusoidal (9...500 Hz)
Humidity	0...93 % rel. humidity	Housing main material	Brass, PC UL 94 V0
Insulation cross-section, min.	0.85 mm	Insulation cross-section, max.	1.05 mm
Category	Cat.6A / Class E <sub>A</sub> (ISO/IEC 11801 2010)	Contact material	Phosphorus bronze
Contact surface	Gold over nickel, Au ≥ 0.8 µm, Ni 2.54 µm	Connection diameter, solid	0.4...0.51 mm
Wire connection diameter, solid, min.	0.4 mm	Conductor connection cross-section, solid (AWG)	AWG 26/1...AWG 24/1
Wire connection diameter, solid, max.	0.51 mm	Connection diameter, flexible	0.46...0.61 mm
Wire cross-section, solid, min. (AWG)	AWG 26/1	Wire cross-section, solid, max. (AWG)	AWG 24/1
Conductor connection cross-section, flexible (AWG)	AWG 27/7...AWG 24/7	Wire connection diameter, flexible, min.	0.46 mm
Wire connection diameter, flexible, max.	0.61 mm	Wire cross-section, finely stranded, min. (AWG)	AWG 27/7
Wire cross-section, finely stranded, max. (AWG)	AWG 24/7	Sheath diameter, min.	5 mm
Sheath diameter, max.	7.3 mm	Shielding	360° all-round enclosure
Protection degree	IP67 with housing	Plugging cycles	750

## Electrical properties

Contact resistance	≤ 20 mΩ	Current-carrying capacity at 50 °C	1 A
Dielectric strength, contact / contact	≥ 1000 V DC	Dielectric strength, contact / shield	≥ 1500 V DC
Insulation strength	500 MΩ	PoE / PoE+	conforming to IEEE 802.3af

## General standards

Certificate No. (cURus)	E316369	Connector standard	IEC 60603-7-51
IP protection classes	IEC 60529	UL standard for communication accessories	UL 1863

## Classifications

ETIM 6.0	EC001121	ETIM 7.0	EC001121
ECLASS 9.0	27-44-03-90	ECLASS 9.1	27-44-03-90
ECLASS 10.0	27-44-03-90	ECLASS 11.0	27-44-03-90

Creation date March 26, 2021 3:35:53 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

2

**Data sheet**

**IE-PI-RJ45-TH**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

**Technical data**

**Approvals**

Approvals



ROHS	Conform
UL File Number Search	E316369

**Downloads**

Approval/Certificate/Document of Conformity	<a href="#">GOST Approval</a> <a href="#">ISO/IEC EN and TIA/EIA Screened Class EA Category 6A, 4 connector channel</a> <a href="#">CC-Link IE-PI-RJ45-TH</a>
Engineering Data	<a href="#">STEP</a>
User Documentation	<a href="#">MAN IE GUIDE DE</a> <a href="#">MAN IE GUIDE EN</a> <a href="#">Designation key / Type key</a>


**IE-PI-RJ45-TH**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

**Drawing**



**Dimensioned drawing**

