



Main

| | |
|---------------------------|---------------------------------------|
| Range of product | Modicon TSX Micro automation platform |
| Product or component type | Modular base controller |
| Primary voltage | 100...240 V 90...264 V AC |
| Input current | 2 mA < 60 A |
| Immunity to micro-breaks | < 20 ms |
| Output current | 0.5 A |

Complementary

| | |
|------------------------------------|--|
| Number of slots | 2 |
| Module type | Screw terminal discrete I/O |
| Discrete input number | 16 24 V AC |
| Discrete output number | 12 relay |
| Integrated connection type | 1 Modbus Modbus RTU 19.2 kbit/s 1 serial link Uni-Telway 19.2 kbit/s |
| Realtime clock | With |
| Memory description | Flash 15 Kwords data Internal RAM 14 Kwords data |
| Maximum size of object areas | 256 %Mi 1 %MWi internal words 128 %KWi constant words |
| Execution time per instruction | 4.81 µs arithmetic REAL floating without PCMCIA card 0.25 µs Boolean without PCMCIA card |
| Execution time for 1 K instruction | 0.25 65 % Boolean and 35 % numerical without PCMCIA card 3.03 100 % Boolean without PCMCIA card |
| Application structure | 1 fast task 1 master task 8 event tasks |
| System overhead | 1.9 ms master task |
| Protection type | Overload protection Short-circuit |
| Network frequency | 50...60 Hz |
| Total useful secondary power | 24 W |
| Electromagnetic compatibility | Immunity to electromagnetic interference IEC 61131-2 Damped oscillatory wave IEC 1000-4-12 Immunity to impulse waves IEC 1000-4-5 Resistance to fast transient IEC 1000-4-4 level 3 Electromagnetic field immunity test IEC 1000-4-3 level 3 Electrostatic discharge IEC 1000-4-2 level 3 |

Environment


| | |
|---------------------------------------|---|
| Ambient air temperature for operation | 0...60 °C |
| Ambient air temperature for storage | -25...70 °C |
| Relative humidity | 5...95 % without condensation for operation 10...95 % without condensation for operation |
| Operating altitude | 0...2000 m |
| Width | 282.7 mm |
| Height | 151 mm |

| | |
|----------------|---------|
| Depth | 152 mm |
| Product weight | 1.91 kg |

Offer Sustainability


| | |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS (date code: YYWW) | Will not be Compliant |
| REACH | Reference not containing SVHC above the threshold |

Dimensions



- (1) PLC empty.
- (2) With screw terminal block.
- (3) With HE10 or SubD connector.

Side View



Use 4 screws with M4x16AF1-VA416 captive washers and 4 M4 AF1-EA4 clip nuts.