

TS 32X15 2M/CRN**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Product image**Building installation wiring**

For building installations, we offer a complete system that revolves around the 10×3 copper rail and comprises perfectly coordinated components: from installation terminal blocks, neutral conductor terminal blocks and distribution terminal blocks to comprehensive accessories such as busbars and busbar holders.

General ordering data

Version	Rail, TS 32, without slot, Stainless steel, rust-proof, untreated
Order No.	0293220000
Type	TS 32X15 2M/CRN
GTIN (EAN)	4032248014026
Qty.	2 m

Creation date March 22, 2021 9:52:11 AM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

TS 32X15 2M/CRN

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	15 mm	Depth (inches)	0.591 inch
Height	33 mm	Height (inches)	1.299 inch
Net weight	701 g	Width	2,000 mm
Width (inches)	78.74 inch		

Mounting rail

Installation advice Direct mounting

Length of the terminal rail	min.	0 mm
	max.	2,000 mm
	nominal	2,000 mm

Material Stainless steel, rust-proof

Pre-punched mounting rail No

Slit gap

Slit length

Slit width

Standards DIN EN 60715

Surface finish untreated

Thickness 1.5 mm

Classifications

ETIM 6.0	EC001285	ETIM 7.0	EC001285
ECLASS 9.0	27-40-06-02	ECLASS 9.1	27-40-06-02
ECLASS 10.0	27-40-06-02	ECLASS 11.0	27-40-06-02

Approvals

ROHS Conform

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S
User Documentation	StorageConditionsTerminalBlocks