



Main

| | |
|--------------------------------|--|
| Range of product | Osiswitch |
| Series name | Universal |
| Product or component type | Limit switch |
| Device short name | XCKD |
| Sensor design | Compact form E CENELEC EN 50047 |
| Body type | Fixed |
| Head type | Plunger head |
| Material | Metal |
| Movement of operating head | Linear |
| Type of operator | Spring return roller lever plunger thermoplastic |
| Switch actuation | By 30° cam |
| Type of approach | Lateral approach 1 direction |
| Electrical connection | Screw-clamp terminals , 1 x 0.34...2 x 1.5 mm ² |
| Cable entry | 1 entry tapped for 1/2" NPT cable gland |
| Number of poles | 2 |
| Contacts type and composition | 1 NC + 1 NO |
| Contacts operation | Snap action |
| Positive opening | With |
| Positive opening minimum force | 18 N |
| Minimum force for tripping | 6 N |

Complementary

| | |
|--|--|
| Body material | Zamak |
| Head material | Zamak |
| Contacts insulation form | Zb |
| Maximum actuation speed | 1 m/s |
| Contact code designation | A300 AC-15 240 V 3 A EN/IEC 60947-5-1 appendix A 10 A Q300 DC-13 250 V 0.27 A EN/IEC 60947-5-1 appendix A |
| [Ui] rated insulation voltage | 300 V UL 508 300 V CSA C22-2 No 14 500 V 3 IEC 60947-1 |
| Resistance across terminals | ≤ 25 mOhm IEC 60255-7 category 3 |
| [Uimp] rated impulse withstand voltage | 6 kV IEC 60947-1 6 kV IEC 60664 |
| Short circuit protection | 10 A cartridge fuse gG |
| Electrical durability | 5000000 cycles DC-13, 24 V 10 W, ≤ 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles DC-13, 48 V 7 W, ≤ 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles DC-13, 120 V 4 W, ≤ 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
| Mechanical durability | 15000000 cycles |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

| | |
|--|---|
| Shock resistance | 50 gn 11 ms IEC 60068-2-27 |
| Vibration resistance | 25 gn 10...500 Hz IEC 60068-2-6 |
| IK degree of protection | IK06 EN 50102 |
| Class of protection against electric shock | Class I IEC 61140 Class I NF C 20-030 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...70 °C |
| Protective treatment | TC |
| Product certifications | CCC CSA UL |
| Standards | CSA C22-2 No 14 EN 60204-1 EN 60947-5-1 IEC 60204-1 IEC 60947-5-1 UL 508 |
| RoHS EUR conformity date | 4Q2009 |
| RoHS EUR status | Will be compliant |