

**CABTITE FR 24/10 BK**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

www.weidmueller.com

**Similar to illustration**

The frame, fabricated from a single piece, is quick and easy to assemble and consists of dimensionally stable, fibre-glass reinforced plastic. The captive foamed seal guarantees effective IP66 sealing in accordance with DIN EN 60529, even on painted and rough surfaces.

**General ordering data**

Version	Frame, Cabtite (cable entry system), Polyamide, glass fibre-reinforced, Deep black, Height: 70 mm, Width: 153 mm, Depth: 19.6 mm, -40 °C...120 °C, IP54, IP65, IP66
Order No.	<a href="#">2583800000</a>
Type	CABTITE FR 24/10 BK
GTIN (EAN)	4050118616682
Qty.	1 pc(s).

Creation date March 29, 2021 7:53:57 PM CEST

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

**CABTITE FR 24/10 BK****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

Depth	19.6 mm	Depth (inches)	0.772 inch
Diameter	5.5 mm	Height	70 mm
Height (inches)	2.756 inch	Height of lowest version	19.6 mm
Mounting dimension - height	130 mm	Mounting dimension - width	32 mm
Net weight	60.95 g	Width	153 mm
Width (inches)	6.024 inch		

**General information**

Halogen	No	Material	Polyamide, glass fibre-reinforced
Opening length	113.5 mm	Opening width	46 mm
Sealing		Sealing element	2 large sealing elements and 4 small sealing elements or 1 large sealing element and 6 small sealing elements or 10 small sealing elements
	TPE		
Silicone	No	Tightening torque	3 Nm
UL 94 flammability rating	V-0		

**Classifications**

ETIM 6.0	EC002624	ETIM 7.0	EC002624
ECLASS 9.0	27-18-28-15	ECLASS 9.1	27-18-92-65
ECLASS 10.0	27-18-28-15	ECLASS 11.0	27-18-28-15

**Approvals**

Approvals



ROHS	Conform
UL File Number Search	E223801

**Downloads**

Engineering Data	<a href="#">STEP</a>
Engineering Data	<a href="#">EPLAN</a>
User Documentation	<a href="#">Cabtite Installation Instructions</a>

**CABTITE FR 24/10 BK**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

Drawings

**Dimensioned drawing**

