

SM 27/12.5 MM WS

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Prevention of incorrect operation: SM

MultiMark device markers can be used with marking materials from different manufacturers. Wherever they are used, they ensure that all components, such as control and signalling devices from different vendors, are clearly assigned.

Your benefits with MultiMark

- “Different materials for various requirements”
- Can be used with equipment from many manufacturers
- Device markers with a familiar design

General ordering data

| | |
|--------------------|---|
| Version | SwitchMark, Device markers, {Reference (AttributeDefinition) not found: pAttr74196859207437}, white |
| Order No. | 2006500000 |
| Type | SM 27/12.5 MM WS |
| GTIN (EAN) | 4050118391367 |
| Qty. | 1,000 pc(s). |
| compatible printer | 2599430000 2599440000 |

Creation date March 26, 2021 8:44:41 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

SM 27/12.5 MM WS

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|----------------|------------|-----------------|------------|
| Depth | 0.1 mm | Depth (inches) | 0.004 inch |
| Height | 12.5 mm | Height (inches) | 0.492 inch |
| Net weight | 0.115 g | Width | 27 mm |
| Width (inches) | 1.063 inch | | |

Temperatures

| | |
|-----------------------------|--------------|
| Operating temperature range | -40...120 °C |
|-----------------------------|--------------|

General data

| | | | |
|-----------------------------------|-------------------|-----------------------------------|-------------------------------|
| Adhesive | Acrylate adhesive | Approval acc. to UL 969 | Yes |
| Colour | white | Halogen | No |
| Material | Polyester | Number of markers per combination | 1 Label reel = Device markers |
| Number per roll | 1,000 | Operating temperature range | -40...120 °C |
| Operating temperature range, max. | 120 °C | Operating temperature range, min. | -40 °C |
| UL 94 flammability rating | V-0 | Version | halogen-free, Self-adhesive |
| Width | 27 mm | | |

Device markers

| | |
|---------|----|
| Halogen | No |
|---------|----|

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC001288 | ETIM 7.0 | EC001288 |
| ECLASS 9.0 | 27-40-06-29 | ECLASS 9.1 | 27-40-06-29 |
| ECLASS 10.0 | 27-40-06-29 | ECLASS 11.0 | 27-28-11-04 |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|------------------|-----------------------------|
| Engineering Data | STEP |
| Engineering Data | EPLAN_WSCAD |

Data sheet

SM 27/12.5 MM WS

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

