

VPU I 1 N-PE 260V/100KA**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Type I lightning/surge protection Suitable as N-PE arrester**

- Pluggable N-PE arrester
- High energy absorption with short time to sparkover
- Installation in distribution board
- Lower residual voltage

General ordering data

Version	Surge voltage arrester, Low voltage, without telecomm. contact, TT nur für N-PE
Order No.	1351920000
Type	VPU I 1 N-PE 260V/100KA
GTIN (EAN)	4050118158281
Qty.	1 pc(s).

Creation date March 23, 2021 5:48:17 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

VPU I 1 N-PE 260V/100KA

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	69 mm	Depth (inches)	2.717 inch
Height	94 mm	Height (inches)	3.701 inch
Mounting dimension - height	75 mm	Net weight	266 g
Width	35.6 mm	Width (inches)	1.402 inch

Temperatures

Storage temperature	-40 °C...80 °C	Operating temperature	-40 °C...70 °C
Humidity	5 - 95% rel. humidity		

General data

Colour	black, blue	Design	Installation housing; 2TE, Insta IP 20
Optical function display	No	Protection degree	IP20
Rail	TS 35	Segment	Power distribution
Suitable for	Count-in installation (leakage current free)	UL 94 flammability rating	V-0
Version	without telecomm. contact		

Insulation coordination acc. to EN 50178

Pollution severity	2	Surge voltage category	IV
--------------------	---	------------------------	----

Rated data IEC / EN

Discharge current I_{max} (8/20 μ s) N-PE	100 kA	Discharge current I_n (8/20 μ s) N-PE	100 kA
Frequency range, max.	60 Hz	Frequency range, min.	50 Hz
Fuse	Not required	Leakage current at U_n	1 μ A
Lightning test current, I_{imp} (10/350 μ s) (N-PE)	100 kA	Low voltage network	TT nur für N-PE
Max. continuous voltage, U_c (N-PE)	260 V	Number of poles	1
Protection level U_p at I_N (N-PE)	≤ 1.6 kV	Rated load current I_L	100 A
Rated voltage (AC)	230 V	Requirements category acc. to IEC 61643-11	Type I, Type II
Requirements class, acc. to EN 61643-11	T1, T2	Response time	≤ 100 ns
Signalling contact	No	Standards	IEC61643-11, EN61643-11
Suitable for	Count-in installation (leakage current free)	Temporary surge voltage (over-voltage) - TOV	1,200 V
Voltage type	AC		

VPU I 1 N-PE 260V/100KA

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Connection data

Type of connection	Screw connection	Stripping length, rated connection	15 mm
Tightening torque, min.	2 Nm	Tightening torque, max.	3 Nm
Clamping range, rated connection	16 mm ²	Clamping range, min.	4 mm ²
Clamping range, max.	35 mm ²	Wire cross-section, solid, min.	2.5 mm ²
Wire cross-section, solid, max.	16 mm ²	Wire connection cross section, finely stranded, min.	2.5 mm ²
Wire connection cross section, finely stranded, max.	25 mm ²	Conductor cross-section, flexible, AEH (DIN 46228-1), min.	2.5 mm ²
Conductor cross-section, flexible, AEH (DIN 46228-1), max.	50 mm ²	Connection cross-section, stranded, min.	2.5 mm ²
Connection cross-section, stranded, max.	50 mm ²		

Classifications

ETIM 6.0	EC000941	ETIM 7.0	EC000941
ECLASS 9.0	27-13-08-05	ECLASS 9.1	27-13-08-05
ECLASS 10.0	27-13-08-05	ECLASS 11.0	27-13-08-05

Tender specification sheets

Long specification	Pluggable Class I arrester made from V0 material for LPL I/II/III/IV with 100 kA, suitable for TN-S, IT or TT mains systems for protection between N and PE. Protection level < 2 kV. Type: Weidmüller VPU I 1 N-PE 260 V/100 kA Order No. 1351920000 or equivalent	Short specification	Class I arrester for LPL I/II/III/IV with 100 kA suitable for TN-S, IT or TT mains systems for protection between N and PE. Protection level < 2 kV. Type: Weidmüller VPU I 1 N-PE 260 V/100 kA Order no. 1351920000 or equivalent
--------------------	---	---------------------	--

Approvals

Approvals



ROHS

Conform

Downloads

Approval/Certificate/Document of Conformity	EAC VPU SERIES CE PAPER Declaration of Conformity
Engineering Data	STEP
Engineering Data	EPLAN_WSCAD


VPU I 1 N-PE 260V/100KA

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Electric symbol



Schematic circuit diagram