

IE-FM5Z2LO0005MST0ST0-X

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com



Assembled IE cables, FO

General ordering data

| | |
|------------|---|
| Version | Patch cable, ST IP 20, ST IP 20, 50 µm, LSZH, 5 m |
| Order No. | 1433990050 |
| Type | IE-FM5Z2LO0005MST0ST0-X |
| GTIN (EAN) | 405011824275 1 |
| Qty. | 1 pc(s). |

Creation date March 23, 2021 10:44:39 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

IE-FM5Z2LO0005MST0ST0-X

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|------|-----------------|-------------|
| Length | 5 m | Length (inches) | 196.85 inch |
| Net weight | 96 g | | |

Temperatures

| | |
|-----------------------|----------------|
| Operating temperature | -20 °C...70 °C |
|-----------------------|----------------|

Cable specific standards

| | | | |
|--|-------------|---|-------------------------------|
| Specification for checking the symmetrical communication cabling | IEC 61935-3 | Specification for twisted-pair device connection cables | IEC 61156-6, DIN EN 50288-4-2 |
|--|-------------|---|-------------------------------|

General standards

| | |
|--------------------|--------------|
| Connector standard | IEC 60874-10 |
|--------------------|--------------|

Standards

| | |
|--------------------|--------------|
| Connector standard | IEC 60874-10 |
|--------------------|--------------|

Fibre-optic

| | | | |
|-------------|---|-----------|---|
| Attenuation | ≤2.5 dB/km at 850 nm, ≤0.7 dB/km at 1300 nm | Bandwidth | ≥ 500 MHz*km at 850 nm, ≥ 500 MHz*km at 1300 nm |
| Fibre type | GOF, Multimode, OM2 | | |

Cable structure

| | | | |
|-----------------------|--------------|------------------|--------|
| Cable layout | ZIPCORD | Core diameter | 50 µm |
| Material sheath | LSZH | Primary coating | 245 µm |
| Sheath diameter | 2.8 * 5.7 mm | Sheathing colour | orange |
| Standard designations | I-V(ZN)H | | |

Mechanical and material properties of cable

| | | | |
|---------------------------------|-------|--------------------------------|-------|
| Halogen | No | Min. bending radius, once only | 28 mm |
| Min. bending radius, repetitive | 56 mm | | |

Plug, left

| | |
|----------------|----------|
| Connector left | ST IP 20 |
|----------------|----------|

Plug, right

| | |
|-----------------|----------|
| Connector right | ST IP 20 |
|-----------------|----------|

plug

| | | | |
|----------------|----------|-----------------|----------|
| Connector left | ST IP 20 | Connector right | ST IP 20 |
|----------------|----------|-----------------|----------|

IE-FM5Z2LO0005MST0ST0-X

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC002607 | ETIM 7.0 | EC002607 |
| ECLASS 9.0 | 27-06-10-03 | ECLASS 9.1 | 27-06-10-03 |
| ECLASS 10.0 | 27-06-10-03 | ECLASS 11.0 | 27-06-10-03 |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|--------------------|--|
| User Documentation | MAN IE GUIDE DE MAN IE GUIDE EN |
|--------------------|--|

Data sheet

IE-FM5Z2LO0005MST0ST0-X

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Detailed drawing

