



Figure similar

MLFB-Ordering data

1FK7063-2AF74-1EG0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

Rated speed (100 K)	3000 rpm
Number of poles	8
Rated torque (100 K)	7.3 Nm
Rated current	5.6 A
Static torque (60 K)	9.10 Nm
Static torque (100 K)	11.0 Nm
Stall current (60 K)	6.50 A
Stall current (100 K)	8.00 A
Moment of inertia	14.700 kgcm ²
Efficiency	91.0 %

Physical constants

Torque constant	1.37 Nm/A
Voltage constant at 20° C	90.5 V/1000*min ⁻¹
Winding resistance at 20° C	0.64 Ω
Rotating field inductance	8.5 mH
Electrical time constant	13.40 ms
Mechanical time constant	1.48 ms
Thermal time constant	40 min
Shaft torsional stiffness	34000 Nm/rad
Net weight of the motor	11.1 kg

Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	63
Cooling	Natural cooling
Radial runout tolerance	0.040 mm
Concentricity tolerance	0.10 mm
Axial runout tolerance	0.10 mm
Vibration severity grade	Grade A
Connector size	1
Degree of protection	IP64
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	Standard (Anthracite RAL 7016)
Holding brake	without holding brake
Shaft extension	Plain shaft
Encoder system	Encoder AM2048S/R: absolute encoder 2048 S/R, 4096 revolutions multi-turn, with EnDat interface

MLFB-Ordering data

1FK7063-2AF74-1EG0

Figure similar

Optimum operating point		Recommended Motor Module	
Optimum speed	3000 rpm	Rated inverter current	9 A
Optimum power	2.3 kW	Maximum inverter current	27 A
Limiting data		Maximum torque	34.00 Nm
Max. permissible speed (mech.)	7200 rpm		
Max. permissible speed (inverter)	6400 rpm		
Maximum torque	35.0 Nm		
Maximum current	28.0 A		