

PRODUCT-DETAILS

6819/39-183-500

6819/39-183-500 Busch-Presence detector Universal, slave, DALI 12 meters



General Information

Extended Product Type	6819/39-183-500
Product ID	2CKA006800A2793
EAN	4011395218242
Catalog Description	6819/39-183-500 Busch-Presence detector Universal, slave, DALI 12 meters
Long Description	DALI slave presence detector for extension of the detection range of DALI master presence detectors. For the supply of operating voltage via the DALI master. Power consumption on the DALI bus: max. 10 mA, corresponds to approx. 5 DALI operating devices. The communication with the DALI master is carried out via the DALI interface. Detection range (for installation height of 3 m): circular Seated persons: up to Ø 10 m, walking persons: up to Ø 12 m. Visible height 23 mm. Ceiling installation using integrated spring bracket. Twist protection via additional quick tensioning. Surveillance density: 72 sectors with 640 switching segments. Suitable for false ceilings with a board thickness from 9 to 25 mm. Hole size: Ø 68 mm.

Ordering

EAN	4011395218242
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

Dimensions

Product Net Width	0.094 m
Product Net Height	0.094 m
Product Net Depth /	0.072 m

Length

Product Net Weight	0.141 kg
--------------------	----------

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	0.141 m
Package Level 1 Height	0.095 m
Package Level 1 Depth / Length	0.165 m
Package Level 1 Gross Weight	272 g
Package Level 1 EAN	4011395218242

Environmental

RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
-------------	---

Additional Information

Auxiliary Voltage AC/DC	9.5 V AC/DC 22.5 V AC/DC
Brand / Label	ABB
Color	aluminium silver
Connection Type	Plug Clamp
Degree of Protection	IP40
Material	Material quality: Thermoplastic Material: Plastic
Mounting Type	Flush Mounted
Product Main Type	Busch-Presence detector Universal, slave, DALI
Product Name	Busch-Presence detector Universal, slave, DALI 12 meters
Product Range	Movement detector
Rated Voltage (U _r)	16 V
RoHS Date	20150727
Surface Finishing	Surface protection: Lacquered Surface finishing: Matt

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	2CKA001473B9577
Declaration of Conformity - CE	2CKA200000E6534
RoHS Information	9AKK104295D8727

Classifications

ETIM 5	EC000133 - Movement sensor complete
ETIM 6	EC000133 - Movement sensor complete
ETIM 7	EC000133 - Movement sensor complete
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → StandAlone Electronics → Presence Detector → Presence Detector Series → Slave Devices → Presence Detector Universal, DALI Slave

