

PRODUCT-DETAILS

2/0UF2020

2/0UF2020 Flush m. wall cabinet 30min.



General Information

| | |
|-----------------------|--|
| Extended Product Type | 2/0UF2020 |
| Product ID | 2CPX040020R9999 |
| EAN | 4011617400202 |
| Catalog Description | 2/0UF2020 Flush m. wall cabinet 30min. |
| Long Description | Fire resistance - wall cabinet, series UF, empty cabinet, for the internal use, with Door, class of protection II (double insulated), degree of protection IP41, fire resistance 30 min tested according to , Reduce fire load 30 min in line with , Maintain functionality 30 min in line with , Rated operational voltage 400V AC 50/60 Hz, surface-coated, in RAL 7035, enclosure out of non flammable material, single-leaf door, door out of non flammable material, with Swivel handle with half cylinder, door opening angle 180 degree, door hinge right, cable entry on top via fire stop cable entry, on bottom via fire stop cable entry, dimensions in mm (H x W x D): 682 x 582 x 205, Grid unit 4 GU, Overall height 0, panel width 2, Space units 96, pre-assembled for installation with Modules, Combi-Sets, CombiLine-Module on EDF-mounting frame |

Ordering

| | |
|------------------------|---------------|
| EAN | 4011617400202 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85381000 |

Dimensions

| | |
|--------------------|--------|
| Product Net Width | 582 mm |
| Product Net Height | 682 mm |

| | |
|----------------------------|--------|
| Product Net Depth / Length | 205 mm |
| Product Net Weight | 58 kg |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | pack 1 piece |
| Package Level 1 Width | 682.000 mm |
| Package Level 1 Height | 582.000 mm |
| Package Level 1 Depth / Length | 205.000 mm |
| Package Level 1 Gross Weight | 58 kg |
| Package Level 1 EAN | 4011617400202 |
| Package Level 2 Units | 12 piece |
| Package Level 2 Width | 830 mm |
| Package Level 2 Height | 1710 mm |
| Package Level 2 Depth / Length | 1210 mm |

Additional Information

| | |
|---------------------------|---|
| Color | light grey |
| Configuration Type | pre-assembled for installation with Modules, Combi-Sets, CombiLine-Module on EDF-mounting frame |
| Cover Plate Type | None |
| Degree of Protection | IP41 |
| DIN Place Units | 96 |
| Enclosure Type | Fire resistance - wall cabinet |
| Enclosure Type of Height | 0 |
| Field Width | 2 |
| Interior Depth | 138 mm |
| Meter Boards | 0 |
| Mounting Type | Flush-mounted |
| Number of Rows | 4 |
| Operational Voltage | 400 V |
| Product Main Type | UF |
| Product Name | 2/OUF2020 Flush m. wall cabinet 30min. |
| Protection Class | Isolated |
| Rated Operational Voltage | Maximum 400 V |

Certificates and Declarations (Document Number)

| | |
|-----------------------------------|------------------------------------|
| Data Sheet, Technical Information | 2CPC000001C0101 2CPC000002C0101 |
| Declaration of Conformity - CE | No declaration needed |
| Environmental Information | 2CPC100001X0201 |
| Instructions and Manuals | 2CPC000186C0201 |

Classifications

| | |
|--------|--------------------------|
| ETIM 4 | EC000058 - Empty cabinet |
| ETIM 5 | EC000058 - Empty cabinet |

| | |
|----------------------------|---------------------------|
| ETIM 6 | EC000058 - Empty cabinet |
| ETIM 7 | EC000058 - Empty cabinet |
| Object Classification Code | U |
| WEEE Category | Product Not in WEEE Scope |

Categories

Low Voltage Products and Systems → Enclosures → Sub Distribution Boards → Fire Resistant Enclosures

