

190 mm

PRODUCT-DETAILS

Package Level 1 Width

416QBS9C Ind. P&S#416QBS9C



General Information	
Extended Product Type	416QBS9C
Product ID	2CMA102906R1000
EAN	7392696029063
Catalog Description	Ind. P&S#416QBS9C
Long Description	Wall mounted Inlet, earthing sleeve position 9h, rated current 16A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code blue, screwless terminals, with cover
Ordering	
EAN	7392696029063
Country of Origin	Turkey (TR)
Minimum Order Quantity	5 piece
Dimensions	
Product Net Width	88 mm
Product Net Height	84 mm
Product Net Weight	0.214 kg
Container Information	

Package Level 1 Depth / Length	265 mm
Package Level 1 Height	230 mm
Package Level 1 Gross Weight	1.411 kg
Package Level 1 EAN	7392696042482
Package Level 1 Units	box 5 piece

Environmental

RoHS Status Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)		
Declaration of Conformity - CE	2CMC700005D0001	
Environmental Information	2CMC000072M0000	
RoHS Information	2CMC700005D0001	
REACH Declaration	2CMC700005D0001	

Additional Information	
Additional Information	3P+N+E
Ambient Temperature	-25 40 °C
Cable Cross-Section	1 2.5 mm²
Color	Blue
Connection Type	Screwless
Degree of Protection	IP44
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz
Function	Inlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#416QBS9C
Mounting Holes	76x48,5
Number of Poles	5
Order Multiple	5 piece
Product Main Type	QBS
Product Name	Wall mounted inlet
Protection Type	Splashproof
Rated Current (I _n)	16 A
Rated Frequency (f)	5060 Hz
Rated Voltage (U _r)	120/208 144/250 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 5015 - Sky Blue

Classifications	
eClass	27440519
UNSPSC	39120000

416QBS9C 3

Categories

Low Voltage Products and Systems \rightarrow Industrial Plugs and Sockets \rightarrow Fast & Safe

